

## TVIHD

## Features

- Converts HD-TVI/AHD/HDCVI/NTSC/PAL/960H signals to HDMI, VGA or Composite Video.
- Supports: 720p@25/30/50/60, 1080p@25/30Hz
- Built-in loopout
- Built-in LED lights on unit to indicate selection
- OSD displayed on monitor to indicate input/output settings
- Includes 12V power supply

## Applications

- Shopper camera awareness
- Simultaneous monitoring
- Entry cameras
- Any installation where HD-analog cameras need to be viewed but not necessarily recorded

## Specifications

Video Input	HD-TVI/AHD/HD-CVI 720p@25/30/50/60Hz, 1080p@25/30Hz, NTSC/PAL/960H
Video Output	HDMI: 720p/60, 1080p/60 VGA: 800x600/60, 1024x768/60, 1280x720/60, 1280x1024/60, 1360x768/60, 1440x900/60, 1600x1200/60, 1680x1050/60, 1920x1080/60
Input Connector	BNC (75Ω1Vpp) x 1
Loop Connector	BNC (75Ω1Vpp) x 1
Output Interface	HDMI Type-A x 1, D-SUB 15 x 1, BNC (75Ω1Vpp) x 1
Switch	Tact Switch x 2

## Operating Specifications

Dimensions ( L x W x H)	3.5" x 5.1" x 1.2"
Power Supply	12V 500mA
Power Consumption	250mA (Max)
Temperature	Operating: 32° to 131 °F (0° to 55°C), Storage: -4° to 185°F (-20° to 85° C)
Humidity	Up to 95%
Weight	0.6 Lbs.

