


HD-TVI Camera In Operating PIR Housing



VL572TPIR 3.7mm pinhole lens, operating PIR, white housing

Features

- Camera encased in working PIR
- Fully adjustable wall/ceiling mount included
- 5 year warranty



Specifications

Image Sensor	1/2.7" Sony CMOS
Resolution.....	1920 x 1080
Minimum Illumination.....	0.001 lux
Electronic Shutter	Auto: 1/60 sec. - 1/100,000 sec.
S/N Ratio	More than 54dB
Day/Night.....	Color/ B/W / Auto
White Balance	Auto
Backlight Compensation.....	Auto/Manual
Gain Control	Auto/Manual
Gamma Correction	0.45/1.0
Video Output.....	1.0Vp-p / 75 ohms
Video System	NTSC System
Power Consumption	120mA (non-operating PIR), 80mA (operating PIR)

Detecting Angle	Max. 100°
Level Signal.....	3.3V/0V
Level Signal Duration	5s to 300s adjustable
Sensor Static Current	<50uA
Detecting Distance	10 ft. to 23 ft. adjustable

Voltage Input.....	12VDC
Power Current	80mA
Operating Temperature.....	4° F – 120° F
Storage Temperature.....	-13° ~ 158°F
Humidity Range	20% ~ 90% RH
Housing	White ABS plastic with mount
Dimensions.....	1.89" (L) x 2.75" (W) x 4.72" (H)
Weight	6.4 oz.