

2MP HD-TVI IR Bullet Camera with Junction Box

VLB5

2.8mm fixed lens, white housing









Features

- Supports up to 2MP @ 30fps
- Full HD resolution over coax
- Supports HD-TVI, CVI, AHD, and 960H Analog
- IR Range: 65' (depending on scene reflection)
- 12VDC Operation (power supply not included)
- IP67 compliant, weather resistant
- Junction box included
- 5 year warranty



Included Junction Box



Camera Specifications		
Image Sensor	1/2.9" CMOS, 2MP	
Minimum Illumination	0 lux (IR ON)	
Image Size	1920 x 1080	
Video Output	AHD/TVI/CVI/CVBS	
Image System	PAL/NTSC	
Electronic Shutter	Auto: 1/50s ~ 1/100000s (PAL); 1/60s ~ 1/100000s (NTSC)	
IR Distance	32.8ft ~ 65.6ft	
Frame Rate	30fps (60Hz); 25fps (50Hz)	
Lens Mount	M12	
S/N Ratio	≥ 52dB (AGC OFF)	

5) 11 Kuno = 526	b (//ee em/	
Functions		
Function Control	OSD (COC Control)	
Day & Night	Yes, Smart IR	
Digital WDR	Yes	
DNR	3D DNR	
AGC	Yes	
Auto White Balance	Yes	
Compensation	BLC	
Front Light Compensation	Yes	
Sharpness	Yes	
Mirror	Yes	
Image Setting	Yes	
Defect Correction	Auto	
Angle Adjustment	Pan (0° ~ 360°); Tilt (0° ~ 80°); Rotation (0° ~ 360°)	

Operating & Unit Specifications

12VDC (power supply not included)
IR OFF: < 1 W; IR ON: < 3 W
-22°F ~ 122°F
10% ~ 95% RH
6.59" (L) x 2.93" (W) x 2.93" (H)
.82 lbs.



Optional Accessories







TVIUTPPT HD Video Transceiver with Pigtail (Balun)



TVIUTP HD Video Transceiver



PMT1 Pole Mount (use with wall mount)







'Camera is defaulted to HD-TVI. ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/26/21