

VLT4DG 2.8mm fixed lens, dark gray housing



Features

- Supports up to 4MP @ 15FPS
- Built-in high powered IR LED's
- Digital Wide Dynamic Range
- 12VDC operation (power supply not included)
- IP66 compliant, weather resistant
- 5 year warranty





Camera Specifications		Operating & Unit Specifications	
Image Sensor	1/2.7"4MP CMOS	Power	12VDC (power supply not included)
Resolution	2MP: TVI, AHD, CVI, CVBS 4MP: TVI, AHD, CVI	Power Consumption	5W
Minimum Illumination	Color: 1 lux, BW: 0.5 lux	Unit Dimensions	2.51" (W) x 2.75" (H) x 7.79" (D)
S/N Ratio	52dB		
WDR	D-WDR / On / Off		
Day/Night	IR cut filter (Auto, Color, B/W, EXT)		
Brightness	1~20		
AGC	0~20		
DNR	2D-DNR (1~16)		
Mirror	Default / H / V / HV		
Remote Control Interface	UTC		

 Remote Control Interface
 UTC

 IR LED
 6 high power LED's





Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 9/24/18

