



Low Loss RP-SMA to N-Type Cable

TEW-L208 (V2.0R)

- RP-SMA male to N-Type male antenna cable
- Extends your wireless antenna up to 8m (26.2 ft.)
- Provides optimal placement for your antenna
- Compatible with directional and omni-directional antennas
- Compatible with 2.4GHz & 5GHz devices


The low loss RP-SMA Male to N-Type Male Cable, model TEW-L208, extends your wireless antenna up to 8m (26.2 ft.) to provide optimal placement. The TEW-L208 can be used with wireless routers, access points and adapters that feature a removable RP-SMA antenna.


Networking Solution




N-type male connector

RP-SMA male connector

 **Interface**
RP-SMA (male) to N-type (male)

 **Compatibility**
Compatible with 2.4GHz (802.11b/g/n) & 5GHz (802.11a/n/ac) devices

 **Installation Flexibility**
8m (26.2 ft.) cable provides optimal placement for your antenna to maximize wireless performance

Specifications

Compatible Standards	<ul style="list-style-type: none"> • IEEE 802.11a/ac • IEEE 802.11b/g/n 	Operating Humidity	<ul style="list-style-type: none"> • Max. 95% non-condensing
Device Interfaces	<ul style="list-style-type: none"> • 1 x N-type male connector • 1 x RP-SMA male connector 	Certifications	<ul style="list-style-type: none"> • CE • FCC
Power	<ul style="list-style-type: none"> • 2.5KW (peak) 	Weight	<ul style="list-style-type: none"> • 340g (0.75 lb.)
Cable length	<ul style="list-style-type: none"> • 8m (26.2 ft.) 	Warranty	<ul style="list-style-type: none"> • 2 year
Cable Loss	<ul style="list-style-type: none"> • 5.05dB 	PACKAGE CONTENTS	
Operating Temperature	<ul style="list-style-type: none"> • -40° - 85° C (-40° - 185° F) 	<ul style="list-style-type: none"> • TEW-L208 	

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.