




Gigabit PoE PD SFP Fiber Media Converter

TFC-PGSFP (v1.0R)


- 1 x 100/1000BASE-T PoE input port
- 1 x 100/1000BASE-SX/LX SFP slot
- PoE Powered – no power adapter is required
- SFP slot accommodates multimode or single-mode modules
- Supports Link Fault Pass-Through (LFPT)
- Jumbo Frame (9KB) Support

TRENDnet's Gigabit PoE PD SFP Fiber Media Converter, model TFC-PGSFP, converts 100/1000BASE-T copper Ethernet to 1000BASE-SX/LX Fiber SFP media and vice versa. The TFC-PGSFP is conveniently powered via PoE switch or injector, no power adapter is required. It features one gigabit PoE input port for power and data, plus one SFP slot that supports both multimode (SX) or single-mode (LX) SFP modules. The SFP slot accommodates both Fast Ethernet and Gigabit SFP modules providing further installation flexibility.




Dual Speed SFP Slot

Dual-speed SFP slot supports both 100Mbps and 1000Mbps SFP modules for multimode or single-mode fiber applications.



PoE Powered


No power adapter required—this fiber SFP converter is powered via an 802.3af/at PoE switch or injector at distances up to 100m (328 ft.).



Compact

Small and compact metal housing design provides greater installation flexibility.

Networking Solution



Ports

1 x 100/1000BASE-T RJ-45 PoE input port, 1 x 100/1000BASE-SX/LX SFP slot



PoE Powered

No power adapter required—this fiber SFP converter is powered via an 802.3af/at PoE switch or injector at distances up to 100m (328 ft.).



Dual Speed SFP Slot

Dual-speed SFP slot supports both 100Mbps and 1000Mbps SFP modules



Jumbo Frame

Sends larger packets, or jumbo frames (up to 9KB), for increased performance

Specifications

Standards	<ul style="list-style-type: none"> • IEEE 802.3 • IEEE 802.3u • IEEE 802.3ab • IEEE 802.3z • IEEE 802.3af • IEEE 802.3at
Device Interface	<ul style="list-style-type: none"> • 1 x Gigabit PoE In port • 1 x 100/1000 Mbps SFP slot • LED indicators
Data Transfer Rate	<ul style="list-style-type: none"> • Ethernet: 10 Mbps (half duplex), 20 Mbps (full duplex) • Fast Ethernet: 100 Mbps (half duplex), 200 Mbps (full duplex) • Gigabit: 2000Mbps (full duplex)
Power	<ul style="list-style-type: none"> • Powered by PoE+ Device • Max. consumption: 2.6W
PoE Delivery	<ul style="list-style-type: none"> • Mode A and B

Operating Temperature	• 0° – 50° C (32° – 122° F)
Operating Humidity	• Max. 90% non-condensing
Dimensions	• 102 x 75 x 23mm (4 x 2.95 x 0.9 in.)
Weight	• 200g (7 oz.)
Certifications	<ul style="list-style-type: none"> • CE • FCC
Warranty	• 3 year warranty

PACKAGE CONTENTS

- TFC-PGSFP
- Quick Installation Guide

All references to speed are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.