



2-Port USB KVM Switch Kit with Audio

TK-209K (v1.2R)

- 2-port KVM switch with VGA and USB connections to computers and audio devices
- Listen to music from one computer while working on the other
- High quality 2048x1536 resolution for a crisp display
- Supports most operating systems and advance mouse designs
- All required cabling included

The 2-Port USB Audio KVM Switch lets you control multimedia PCs with just one keyboard, monitor, mouse, microphone, and a set of speakers. The KVM switch not only allows you to share your monitor, keyboard and mouse but you can also share microphone and speakers. With just a simple press of a button, this KVM switch eliminates the hassle of cable swapping and switching between 2 PCs. With it's Hot-Plug, Auto-Scan and Hot-Key operating features, the TK-209K is the perfect choice for managing 2 PCs. Separate KVM cables are included.

- Control up to 2 computers/servers with one set of console device
- USB keyboard/mouse emulation with 2 sets of detachable KVM cables
- Compliant with Windows and Linux
- High video quality, up to 2048 x 1536 VGA resolution
- Listen to music from one computer while working on the other
- Auto-Scan & LED display for computer monitoring
- Computer selection by face panel push buttons, keyboard hot key commands or Windows-based client switching software*
- User definable hot key (Windows only)
- Plug & Play and hot-pluggable
- USB interface power method
- 2-year limited warranty

Specifications

Hardware

Connections

- 2 computers

USB Interface

- USB 1.1 compliant

KVM Cable

- 2 sets of 1.2m (4ft.) USB KVM cables
- 2 sets of 1.2m (4ft.) audio cables (USB mini B to 3.5mm jack)

Cable Interface (all male)

- To KVM
 - KVM Cable: 1 x VGA/SVGA HDB 15-pin
 - Audio Cable: 1 x USB (Mini B)
- To PC
 - KVM Cable: 1 x USB (Type A), 1 X VGA/SVGA HDB 15-pin
 - Audio Cable: 1 x 3.5mm speaker jack, 1 x 3.5mm microphone in jack

PC Port Connectors (all female)

- 2 x VGA/SVGA HDB 15-pin
- 2 x USB (Mini B)

Console Port Connectors (all female)

- 1 x USB keyboard (type A)
- 1 x USB mouse (type A)
- 1 x VGA/SVGA HDB 15-pin
- 1 x 3.5mm speaker jack
- 1 x 3.5mm microphone jack

Supported OS

- Windows and Linux

Port Selection

- Front panel push buttons, keyboard hot key commands or Windows-based Client Switching software*

Auto-Scan Interval

- 10 ~ 60 seconds

Keyboard Status

- Save and restore

Power Type

- USB Interface Power

Dimensions

- 98 x 70 x 28mm (3.86 x 2.76 x 1.1in.)

Weight

- 100 g (3.6oz)

Temperature

- Operating: 0°C ~ 40°C (32°F ~104°F)
- Storage: -20°C ~ 60°C (-4°F ~140°F)

Humidity

- 0%~90%, non-condensing

Certifications

- CE, FCC

Package Contents

- TK-209K
- Quick Installation Guide
- 2 sets of USB KVM cables (1.2m/4ft)
- 2 sets of audio cables (1.2m/4ft.)

*For optimal performance, we recommend using a wired keyboard and mouse. Please go to <http://www.trendnet.com/downloads> to download the client switching software.