


4-Port USB 3.0 Hub

TU3-H4 (v3.0R)

- · Easy installation
- Add four SuperSpeed 5Gbps USB 3.0 ports
- · Convenient 1m (3 ft.) USB 3.0 cable
- · Backward compatible with USB 2.0 and 1.1 devices
- Full power for all USB ports with included power adapter


TRENDnet's 4-Port USB 3.0 Hub, model TU3-H4, instantly adds four 5Gbps SuperSpeed USB 3.0 ports to a computer. Easy installation – simply plug in flash drives, printers, scanners and other USB 3.0 devices at speeds ten times faster than a USB 2.0 connection. The TU3-H4 USB 3.0 hub is also backwards compatible with USB 2.0 and 1.1 devices.

TRENDIET




Included Power Adapter

Power adapter provides a total power of 20W.



USB 3.0

Easily connect up to four USB 3.0 devices to a USB 3.0 enabled desktop or notebook PC.



USB Cable

Included 1m (3 ft.) USB 3.0 cable accommodates most installation scenarios.





Easy Setup

No CD installation



Operating Systems

Compatible with Windows, Mac and Linux operating systems



Power Adapter

Power adapter provides a total power of 20W



USB 3.0

Easily connect up to four USB 3.0 devices to a USB 3.0 enabled desktop or notebook PC



Installation Flexibility

Included 1m (3 ft.) USB 3.0 cable accommodates most installation scenarios.



Backwards Compatibility

USB 3.0 hub is compatible with USB 2.0 and 1.1 devices



LED Indicator

LED indicator confirms USB connectivity



Specifications

| • | |
|----------------------|---|
| Standards | • USB 3.0 • USB 2.0 • USB 1.1 |
| Interfaces | 4 x Type-A USB 3.0 ports1 x Type-B micro USB 3.0 portPower portLED indicator |
| Maximum Data Rate | • Up to 5Gbps |
| Special Features | Compact form factor Flexible USB 3.0 cable Full power to connected devices |
| Power adapter | Input: 100-240V, 50/60Hz Output: 5V DC, 4A Consumption: Max. 20 Watts |
| USB bus powered | Output: 5V DC, 0.9A Consumption: Max. 4.5 Watts |
| USB Charging | Standard Mode Max. 0.9A total for all USB ports Fast Charge Mode (with optional power adapter) Max. 1.5A per port for Battery Charging 1.2 compliant devices Max. 2.4A per port for Smartphone/Tablet |

| Operating Temperature | • 0° - 40° C (32° - 104° F) |
|--------------------------|---|
| Operating Humidity | Max. 90% non-condensing |
| Certifications | • CE • FCC |
| Dimensions | • 75 x 51 x 14.5mm (2.95 x 2.01 x 0.57 in.) |
| Weight | • 42g (1.48 oz.) |
| Warranty | • 2-year limited |

PACKAGE CONTENTS

- TU3-H4
- USB 3.0 Cable (1m / 3 ft.)
- · Quick Installation Guide
- Power adapter (5V DC, 4A)