

AUDIO CABLE

14 AWG / 4 Conductor



Description

14/4 Stranded CMR/CL3R Sound Audio Cable

Applicable Standards

- For Communication and Signal Control Systems
- 4 Oxygen Free Bare Copper Conductors in an Overall Jacket

Physical Characteristics

Conductor		Oxygen Free B.C.
Number of Conductors		4
AWG		14
Stranding		105
Diameter	(inches)	0.0063
Insulation		PVC
Diameter	(inches)	0.1023
Average Thickness	(inches)	0.014
Min. Point Thickness	(inches)	0.013
Assembly Diameter	(inches)	0.248
Jacket		PVC
Outer Diameter	(inches)	0.3149
Average Thickness	(inches)	0.0315
Min. Point Thickness	(inches)	0.0283
Rip Cord		Nylon
Conductor Resistance	(Ohms)	9.2
Nominal Weight	(pounds)	42

Colors

Insulation Colors Black / Red / White / Green

Part Numbers

Part Number	Color		Put-up
AC1404RBK4-500	Black	500'	Reelex II
AC1404RWH4-500	White	500'	Reelex II

Cable Marking

AUDIO CABLE 4 COND 14AWG HI-STRAND OFC CMR/CL3R FT4 75C
XXXXXX C(ETL)US ****FT