

16AWG/2C Stranded Riser (CMR) Direct Burial Audio Cable

Cable Detail



Approval



Description

- 16/2 Stranded CMR/CL3R Direct Burial Sound Audio Cable

Applicable Standards

- For Communication and Signal Control Systems
- 2 Oxygen Free Bare Copper Conductors in an Overall Jacket

Physical Characteristics

Conductor	Oxygen Free B.C.
Number of Conductor	2
AWG	16
Stranding	65
Diameter	0.0063 (inches)
Insulation Material	PVC
Diameter	0.0827 (inches)
Nominal Wall	0.0098 (inches)
Jacket Material	FR-PVC
Overall Diameter	0.2008 (inches)
Nominal Thickness	0.0197 (inches)
Paper Tape	YES
Rip Cord	YES
Conductor Resistance	15.8 (ohms/1000m)
Voltage	300 (volts)
Nominal Weight	16 (pounds)
Temperature Rating	-20°C - 70°C

Colors

- Insulation Color
Black / Red
- Jacket Color
Black

Part Number

AC1602OSPBK4-500

Package

500FT / REELEX II

Cable Marking

AUDIO CABLE 2 COND 16 AWG HI-STRAND OXYGEN FREE COPPER CMR/CL3R DIRECT BURIAL AUDIO CABLE SUN RES EXXXXXX C(ETL)US ***FT