

AUDIO CABLE

16 AWG / 4 Conductor



Description

16/4 Stranded CMR/CL3R Sound Audio Cable

Applicable Standards

- For Communication and Signal Control Systems
- 4 Oxygen Free Bare Copper Conductors in an Overall Jacket

Physical Characteristics

Conductor		Oxygen Free B.C.
Number of Conductors		4
AWG		16
Stranding		65
Diameter	(inches)	0.0063
Insulation		PVC
Diameter	(inches)	0.0827
Average Thickness	(inches)	0.0122
Min. Point Thickness	(inches)	0.0106
Assembly Diameter	(inches)	0.2008
Jacket		PVC
Outer Diameter	(inches)	0.248
Average Thickness	(inches)	0.0236
Min. Point Thickness	(inches)	0.0213
Rip Cord		Nylon
Conductor Resistance	(Ohms)	15.5
Nominal Weight	(pounds)	27

Colors

Insulation Colors Black / Red / White / Green

Part Numbers

Part Number	Color		Put-up
AC1604RBK4-500	Black	500'	Reelex II
AC1604RWH4-500	White	500'	Reelex II

Cable Marking

AUDIO CABLE 4 COND 16AWG HI-STRAND OFC CMR/CL3R FT4 75C
XXXXXX C(ETL)US ****FT