

## Landscape Cables



### Description

Underground Circuit Cable

### Applicable Standards

- UL Standard 493 rated to 150V
- OSHA acceptable

AWG Size / Cond.	Stranding	Insulation Thickness	Nominal O.D.
18/2	16/30	0.045	.137 x .270
16/2	26/30	0.045	.150 x .310
14/2	41/30	0.045	.165 x .340
12/2	65/30	0.045	.189 x .384
10/2	104/30	0.045	.212 x .426
8/2	168/30	0.06	.284 x .568

### Construction

Soft Annealed bare copper, bunch strand uncoated copper conductors. Conductors are laid flat and parallel. Insulated with Black PVC 60°C. Polarity is identified by surface ridges Zip cord type.

### Part Numbers

Part Number	Color	Footage	Put-up
LSC1802RBK2	Black	500'	Reel
LSC1602RBK2	Black	500'	Reel
LSC1402RBK2	Black	500'	Reel
LSC1202RBK2	Black	500'	Reel
LSC1002RBK2	Black	500'	Reel
LSC0802RBK2	Black	500'	Reel

### Cable Marking

LSC-XX/2 XX AWG 2C UNDERGROUND LOW ENERGY  
CIRCUIT CABLE 30V C(ETL)US XXXXXXXX SUN RES RoHS XXXXFT