

Security Solid Cable 22 AWG / 2 Conductor



Description

22/2 Solid Bare Copper CMR Security Cable

Applicable Standards

- Class 2 Power Limited Circuit Cable and Communications
- Cable for General Purpose Applications

Physical Characteristics

| Conductor | | Bare Copper |
|--------------------------|----------|-------------|
| Number of Conductors | | 2 |
| AWG | | 22 |
| Insulation | | PVC |
| Avg. Thickness | (inches) | 0.006 |
| Insulated Conductor Dia. | (inches) | 0.037 |
| Jacket | | FR-PVC |
| Avg. Thickness | (inches) | 0.014 |
| Overall Diameter | (inches) | 0.101 |
| Nominal Weight 1000' | (pounds) | 8 |
| Nominal Weight 500' | (pounds) | 4 |

Colors

Insulation Colors **Green, Red**

Part Numbers

| Part Number | Color | | Put-up |
|---------------|-------|--------|-----------|
| SC2202RGY1 | Grey | 1,000' | Box |
| SC2202RWH1 | White | 1,000' | Box |
| SC2202RWH-500 | White | 500' | Coil Pack |

Cable Marking

22AWG 2 COND SOLID XXXXXX CMR FT4 C(ETL)US **FT**